

# Hydrotech® Flex-Flash FV

formerly known as Flex-Flash FV



BUILDING TRUST



## GENERAL DESCRIPTION

Flex-Flash F Vertical is an inorganic, woven, glass fiber fabric with an asphalt coating.

## BASIC USE

Flex-Flash F Vertical is designed to be used as the standard reinforcement material for Hydrotech’s Monolithic Membrane 6125®-FR (fabric reinforced) waterproofing assembly on vertical foundation walls. It is used to reinforce the membrane over the entire substrate. The 10 X 10 open weave allows the two coats of membrane to bond together easily through the fabric. Unadhered pockets between the layers of membrane, that can be common with the regular Flex-Flash F, are eliminated. The regular spunbonded polyester Flex-Flash F is still required for all horizontal and standard reinforcing applications, including inside corners (wall to footing) and outside corners (deck to wall).

Flex-Flash F Vertical is not intended to be used at drains, expansion joints or as an exposed flashing.

## SIZES

Flex-Flash F Vertical is available in a standard width of 36 inches and a standard length of 150 feet.

## TECHNICAL DATA

| PROPERTY                       | TEST METHOD | RESULTS |
|--------------------------------|-------------|---------|
| COLOR                          |             | Black   |
| UNIT WEIGHT (oz/sq yd)         | ASTM D1668  | 2.4     |
| YARN COUNT (per inch)          | ASTM D1668  | 10 X 10 |
| BREAKING STRENGTH avg. (lb/in) | ASTM D1668  | 80 X 90 |

## LEED INFORMATION

|                                | Credit 4 | Credit 5   |
|--------------------------------|----------|------------|
| Recycled Content (% by weight) | 0        |            |
| Manufacture Location           |          | Albion, NY |
| Extraction/Harvesting Location |          | Albion, NY |
| VOC Content (g/L)              |          | 0          |

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.