

Hydrotech® Securock®

formerly known as Securock®



BUILDING TRUST



GENERAL DESCRIPTION

USG Securock Gypsum-Fiber Roof Board, as marketed by American Hydrotech, Inc., is a rigid, square-edged, roof substrate board composed of recaptured gypsum and cellulose fiber. Securock is made with 97% certified recycled content.

BASIC USE

Securock Gypsum-Fiber Roof Board is designed to be used as an acceptable substrate for the application of Hydrotech's Monolithic Membrane 6125®-FR (MM6125-FR) membrane. Securock is secured to minimum 22 gauge structural metal decking with appropriate plates and fasteners (min. 10 per board) or construction adhesives. The 5/8 inch thick Securock panels must be used when securing directly to the metal decking. The 1/2 inch thick Securock may be used when securing through rigid insulation to the metal decking.



SIZES

Securock from Hydrotech is available in standard 4 foot X 8 foot panels and 1/2 inch or 5/8 inch thicknesses.

TECHNICAL DATA

THICKNESS		1/2 inch	5/8 inch
WEIGHT (lb./sq.ft., nominal)		2.3	3.02
FLEXURAL STRENGTH (lb., min., parallel)	ASTM C473	110	161
COMPRESSIVE STRENGTH (psi, nominal)		500	500
FLUTE SPANABILITY (in., max.)	ASTM E661	8	8
PERMEANCE (perms)	ASTM E96	26	24
WATER ABSORPTION (% max.)	ASTM C473	10	10
SURFACE WATER ABSORPTION (grams, nom.)	ASTM C473	1.6	1.6
R VALUE	ASTM C518	0.5	0.6
COEFFICIENT OF THERMAL EXPANSION (inches/inch • °F)	ASTM E831	8 X 10 ⁻⁶	8 X 10 ⁻⁶
LINEAR VARIATION w/CHANGE IN MOISTURE (inches/inch • %RH)	ASTM D1037	8 X 10 ⁻⁶	8 X 10 ⁻⁶
MOLD RESISTANCE	ASTM D3273	10	10

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	97 (pi)	
Manufacture Location		Gypsum, OH
Extraction/Harvesting Locations		85% Conemaugh, PA 15% Freemont, OH
VOC Content (g/L)		0

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.