

Hydrotech® Stone Filter Fabric - White

formerly known as Stone Filter Fabric - White



BUILDING TRUST



GENERAL DESCRIPTION

Stone Filter Fabric is a white, UV stabilized, needle-punched, non-woven polypropylene fabric.

BASIC USE

Stone Filter Fabric is designed to be used in all Protected Membrane Roof (PMR) assemblies as a separator mat between the stone/gravel ballast and Dow STYROFOAM™ insulation. Stone Filter Fabric serves three main functions. 1) It protects the underlying STYROFOAM™ insulation board from exposure to the sun. 2) It prevents the stone/gravel ballast from falling in between the joints in the insulation boards. 3) It prevents individual insulation boards from floating up out of the array.



SIZES

Stone Filter Fabric is available in roll form with dimensions 13.5 feet in width and 360 feet in length (4,860 square feet per roll – approximately 4,500 “effective” coverage with 12 inch side and end laps). Each roll weighs approximately 101 pounds.

TECHNICAL DATA

PROPERTY	TEST METHOD	RESULTS
COLOR		White
UNIT WEIGHT (oz/sq yd)	ASTM D3775	3.0
TENSILE GRAB STRENGTH (lb)	ASTM D4632	95
ELONGATION (%)	ASTM D4632	50
APPARENT OPENING SIZE (U.S. sieve)	ASTM D4751	50
FLOW RATE (gpm/ft ²)	ASTM D4491	150

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Ringgold, GA
Extraction/Harvesting Location		Dayton, TX
VOC Content (g/L)		0

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.