

# Hydrotech® Moisture Retention Mat

formerly known as Moisture Retention Mat



BUILDING TRUST



## GENERAL DESCRIPTION

Moisture Retention Mat is composed of high-quality, non-deteriorating, polypropylene fibers.

## BASIC USE

Moisture Retention Mat is used in the Hydrotech Garden Roof® Assembly to retain moisture for stormwater management.

## INSTALLATION

- Moisture Retention Mat (MRM) shall be installed as indicated in Hydrotech's Garden Roof® Installation Guidelines.



## TECHNICAL DATA

THICKNESS:	3/16 in. (≈200 mils)		
SIZE:	7.5 ft. X 100 ft. (2.3m X 30.5m) - in rolls (715 sq.ft. effective coverage)		
WEIGHT:	16 oz./yd <sup>2</sup> (542 g/m <sup>2</sup> )	0.11 lb./sq.ft. (0.54 kg/sq.m.) - dry;	1.2 lb./sq.ft. (5.9 kg/sq.m.) - wet
WATER RETENTION CAP:	≈0.13 gal./sq.ft. (5.3 l./sq.m.)		
TENSILE STRENGTH: (ASTM D4632)	380 lb (1.69 kN)	ELONGATION: (ASTM D4632)	50%
TRAPEZOIDAL TEAR: (ASTM D4533)	145 lb/in <sup>2</sup> (0.644 kN)	PUNCTURE STRENGTH: 240 lb (1.07 kN) (ASTM D4833)	

## LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Athens, GA
Extraction/Harvesting Location		Garyville, LA
VOC Content (g/L)		0

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.