

Hydrotech® GardenHatch® Inspection Chamber



BUILDING TRUST



formerly known as GardenHatch® Inspection Chamber

GENERAL DESCRIPTION

GardenHatch Inspection Chambers are 18-gauge stainless steel, over-drain inspection boxes, with perforated sides and removable lids. Extensions are available to increase the height for deeper growing media applications.

BASIC USE

GardenHatch Inspection Chambers are specifically designed to be installed over the deck drains, prior to the installation of subsequent Garden Roof® components to allow for maintenance access to the drains.



INSTALLATION

- GardenHatch Inspection Chambers shall be installed as indicated in Hydrotech’s Garden Roof Installation Guidelines.
- The Inspection Chamber may be installed directly on the Gardendrain®, the STYROFOAM™ insulation or directly over the root barrier protection for the MM6125®-FR membrane.
- Vegetation-free zones (i.e., gravel) are typically required around all inspection chambers.
- When deeper assembly depths are encountered, the GardenHatch base element and lid can be combined with extension elements which fit over the sides of the base element to add height as needed.

TECHNICAL DATA

SIZE:	Chamber dimension: 11 in. X 11 in. (28 cm X 28 cm) w/4 in. flanges or 18 in. X 18 in. (45.7 cm X 45.7 cm) w/4 in. flanges
HEIGHT:	4 3/4 in. (12cm)
EXTENSIONS :	1 in. (2.5 cm); 3 in. (7.6 cm); 8 1/2 in. (21.6 cm)
WEIGHT:	7 lb. chamber & lid add 1, 2, and 3 lb. respectively for each extension

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	80 (pi)	
Manufacture Location		Evanston, IL
Extraction/Harvesting Location		Oswego, NY
VOC Content (g/L)		0

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation • Roofing 100 Dan Road, Canton, MA 02021 USA • (888) 509-3350 • 12/24