

# Hydrotech® Hanover Flexible Fixed-Height Pedestal



BUILDING TRUST



formerly known as Hanover Flexible Fixed-Height Pedestal

## GENERAL DESCRIPTION

The Hanover flexible fixed-height pedestal consists of square fixed height EPDM rubber support pedestals with integral joint spacer tabs that can be combined with square leveling shims made of the same flexible EPDM rubber.

## BASIC USE

The Hanover flexible fixed-height pedestal is designed for use with Hanover’s Architectural Pavers to provide a loose-laid, open joint paver installation. Combinations of pedestals and shims can provide elevation of the pavers off the substrate to provide free drainage and air movement beneath the paver surface or to make up for differences in height between the structural deck and the finished elevation.



The flexible pedestals can be used singularly or in combination with the shims to accommodate elevations from 3/8 inch to 2 inches. Shims can be used with the support pedestals in whole, or cut into halves or quarters for minor leveling and elevation adjustments. The flexible pedestals cannot be stacked together.

Both the flexible pedestals and shims plates are easily cut into halves or quarters to accommodate perimeter and corner conditions.

## TECHNICAL DATA

EPDM Pedestal	EPDM Rubber	5 inches square; 3/8 inch thick; 1/8 inch joint spacer tabs
EPDM Shims	EPDM Rubber	5 inches square; 1/16 and 1/8 inch thick

## LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	15 pi	
Manufacture Location		Hanover, PA
Extraction/Harvesting Location		Morristown, NJ
VOC Content (g/L)		0

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKAs Technical Service Department at 1-800-933-7452. Nothing contained in any SIKAs literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKAs product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKAs product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKAs products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.